

LISTING OF THE CLAIMS

The following listing of claims replaces all prior listings of claims:

1. (Currently Amended) A shoe sole with reinforcing structure for an arch of a foot, comprising:

an outer sole;

a midsole attached to a top surface of the outer sole; and

a reinforcing member for reinforcing an arch portion of the midsole, the arch portion covering the arch of the foot,

wherein the midsole is formed of resin foam and has a first arch at a bottom portion of the arch portion of the midsole,

the first arch has a bottom surface,

the outer sole is substantially not attached to the first arch of the midsole,

the reinforcing member has a second arch located at the arch portion of the midsole, a fore end part located in front of the second arch and a rear end part located in the rear of the second arch,

the second arch has a top surface and a bottom surface,

the fore end part of the reinforcing member is bonded to at least either the midsole or the outer sole, in front of the first arch,

the rear end part of the reinforcing member is bonded to at least either the midsole or the outer sole, in the rear of the first arch,

wherein a Young's modulus of the reinforcing member is set to be greater than that a Young's modulus of the first arch of the midsole,

a no member, which is to be a part of the reinforcing member, having a greater Young's modulus than the Young's modulus of the first arch is not affixed to the bottom surface of the first arch,

the reinforcing member is arranged so that portions of the top surface of the second arch and portions of the bottom surface of the first arch are spaced apart from each other with no intervening structure therebetween, and

at least a part of the bottom surface of the first arch is not in contact with at least a part of the top surface of the second arch in vertically spaced relationship to each other,

whereby non-contact areas of the first arch and the second arch are defined and the non-contact areas can be deformed independently from each other at the arch portion of the midsole when impact load of landing is applied.

2. (Currently Amended) A shoe sole with reinforcing structure for an arch of a foot, comprising:

an outer sole having a ground contact surface and a top surface opposite to the ground contact surface;

a midsole having a top surface and a bottom surface, the bottom surface being attached to the top surface of the outer sole and covering the top surface of the outer sole; and

a reinforcing member for reinforcing an arch portion of the midsole, the arch portion covering the arch of the foot,

wherein the midsole has a first arch at a bottom portion of the arch portion of the midsole, the first arch is formed of resin foam and has a bottom surface,

the reinforcing member has a second arch located at the arch portion of the midsole, a fore end part located in front of the second arch and a rear end part located in ~~the~~ a rear of the second arch,

the second arch has a top surface and a bottom surface,

the second arch is located so as to be covered with the first arch,

the fore end part of the reinforcing member is bonded to at least either the midsole or the outer sole in front of the first arch,

the rear end part of the reinforcing member is bonded to at least either the midsole or the outer sole in ~~the~~ a rear of the first arch,

the first arch and the second arch are substantially not attached to the top surface of the outer sole and do not have ground contact when the ground contact surface of the outer sole is grounded,

wherein a Young's modulus of the second arch is set to be greater than ~~that~~ a Young's modulus of the first arch,

~~[[a]] no member, which is to be a part of the reinforcing member, having a greater~~ Young's modulus greater than the Young's modulus of the first arch of the midsole, ~~is not~~ affixed to the bottom surface of the first arch,

the reinforcing member is arranged so that portions of the top surface of the second arch and portions of the bottom surface of the first arch are spaced apart from each other with no intervening structure therebetween, and

at least a part of the bottom surface of the first arch is not in contact with a part of the top surface of the second arch in vertically spaced relationship to each other,

whereby non-contact areas of the first arch and the second arch are defined and the non-contact areas can be deformed independently from each other at the arch portion of the midsole when impact load of landing is applied.

3. (Original) A shoe sole according to Claim 2, wherein when impact load of landing is applied, downward displacement of the non-contact area of the bottom surface of the first arch is set to be larger than that of the non-contact area of the top surface of the second arch.

4. (Original) A shoe sole according to Claim 2, wherein the reinforcing member has two side portions and the two side portions are bonded to the midsole.

5. (Original) A shoe sole according to Claim 2, wherein the bottom surface of the first arch has a first curved surface which forms a concave surface and the top surface of the second arch has a second curved surface which is convex upwards.

6. (Original) A shoe sole according to Claim 2, wherein the bottom surface of the first arch and the top surface of the second arch define a domain, and the domain is formed to be hollow.

7. (Original) A shoe sole according to Claim 2, wherein the bottom surface of the first arch and the top surface of the second arch define a domain, and the domain is filled with a filler which has a smaller Young's modulus than the midsole and which is capable of varying its volume.

8. (Original) A shoe sole according to Claim 6, wherein entire of a peripheral edge of the reinforcing member is bonded to the midsole, thereby to seal the domain.

9. (Original) A shoe sole according to Claim 7, wherein entire of a peripheral edge of the reinforcing member is bonded to the midsole, thereby to seal the domain.

10. (Original) A shoe sole according to Claim 6, wherein an opening passing through the second arch vertically is formed.

11. (Original) A shoe sole according to Claim 2, wherein the first arch is formed of foam of ethylene-vinyl acetate copolymer, and the reinforcing member is formed of non-foam of polyurethane, or foam or non-foam of ethylene-vinyl acetate copolymer.

12. (Original) A shoe sole according to Claim 2, wherein the reinforcing member further comprises medial and lateral side portions on the medial side and lateral side of a foot of the second arch, and the medial and lateral side portions of the reinforcing member are bonded to the midsole.

13. (Previously Amended) A shoe sole according to Claim 2, wherein
the outer sole is separated into a fore foot part and a rear foot part at a position corresponding to the arch of the foot,

the fore foot part and the rear foot part of the outer sole each have a top surface and a bottom surface,

the fore end part of the reinforcing member is sandwiched in between the top surface of the fore foot part of the outer sole and the bottom surface of the midsole, and

the rear end part of the reinforcing member is sandwiched in between the top surface of the rear foot part of the outer sole and the bottom surface of the midsole.

14. (Original) A shoe sole according to Claim 2, wherein
the midsole includes an upper midsole body and a lower midsole body,
the upper and lower midsole bodies are formed of an ethylene-vinyl acetate copolymer,
and
the reinforcing member is bonded to the upper and lower midsole bodies with both of the

fore end part and the rear end part of the reinforcing member sandwiched in between the upper midsole body and the lower midsole body.

15. (Original) A shoe sole according to Claim 2, wherein
the reinforcing member constitutes a first reinforcing member,
a second reinforcing member other than the first reinforcing member is provided, and
the second reinforcing member is arranged below the first reinforcing member.

16. (Original) A shoe sole according to Claim 2, wherein
the center line of the first arch in the longitudinal direction and the center line of the
second arch in the longitudinal direction are arranged at least just under a navicular bone, a
cuboid bone or the cuneiform bone of the foot.

17. (Currently Amended) A shoe sole according to Claim 2, wherein
the first arch has a top surface,
the top surface of the first arch has a ~~third~~ curved surface which is convex upwards so as
to be approximately along with the arch of the foot.

18. (Currently Amended) A shoe sole according to Claim 2, wherein
the bottom surface of the second arch has a ~~fourth~~ curved surface which forms a
concave surface recessed upwards.

19. (Currently Amended) A shoe sole comprising:
a midsole having a foot bearing surface and a bottom surface, the bottom surface
including an arch portion and a remaining portion, the arch portion covering an arch of a foot,
an outer sole having a ground contacting surface and a top surface, the outer sole being
attached to the remaining portion of the bottom surface of the midsole,
a first arch formed in the bottom surface of the midsole at the arch portion, a bottom
surface of the first arch being concave downward, and
a reinforcing member for the arch portion, the reinforcing member comprising:
a second arch, the first and second arches juxtaposed upon each other, the top surface of

the second arch being convex upwards toward the bottom surface of the first arch,

wherein portions of such top surface of the second arch and bottom surface of the first arch are in spaced apart relationship to each other with no intervening structure therebetween and such portions deform independently from each other upon application of an impact load to the sole,

wherein the second arch has a ~~greater~~ Young's modulus greater than a Young's modulus of the first arch, and ~~[[a]] no member, which is to be a part of the reinforcing member, having a~~ greater Young's modulus than Young's modulus of the first arch, is ~~not~~ affixed to the bottom surface of the first arch.

20-41. (Cancelled)